

Proxy-Clean®

Drinking Water System Cleaner
FOR INDUSTRIAL USE ONLY

- Proxy-Clean® prevents and removes heavy soils.

PROXY-CLEAN PRODUCTS
McKinney, TX 75071

PROXY-CLEAN® is a registered trademark
www.proxyclean.com

NET CONTENTS: 1 US GALLON / 3.8 L

DIRECTIONS FOR USE

Purpose: To efficiently remove heavy soils from the drinking water system

CLEANING WHEN THE SYSTEM IS NOT IN USE:

- Determine the capacity of the drinking water system
- Prepare a 1-3% solution, depending on the degree of contamination
- Introduce the solution into the system
- Make sure there is adequate air release
- Remove the cap at the end of the drinking system to check for the fizzing reaction, to determine that Proxy-Clean® has reached every point
- Activate all nipples or cups
- Allow the solution to circulate, if possible
- If circulation is not possible, the system must stand full for a minimum of 12 hours
- After cleaning, thoroughly flush with potable water
- Once again, activate all nipples or cups

CLEANING AN OPERATING SYSTEM (animals present)

Mix Proxy-Clean® with water, to the following stock solution/premix:

Pump setting	Water quantity	Proxy-Clean®
1:128	5 gallon	8 oz.

If cleaning has to be done when animals are present, start with a dosage of 8 ounces of Proxy-Clean® per 5 gallons of water.
For heavier cleaning, the dosage may be raised until a maximum of 20 ounces of Proxy-Clean® per 5 gallons of water is reached.